

YDPU2.E245489 - Tubing, Extruded Insulating - Component

Tubing, Extruded Insulating - Component

BM SPA
 VIA MILANO 54/56
 ROZZANO, MI 20089 Italy

E245489

Cat. No.	Voltage Rating	Temperature Rating, °C	Color	Oil-resistance Class	VW-1 Flame
Flexible Heat shrinkable Polyolefin tubing with meltable liner					
GBA	600	125	All except clear	None	Yes
Shrinkable Polyolefin - Flexible					
GBS	600	125	ALL color except clear	-	Yes

Marking: Company name, catalog designation, temperature rating in degrees Celsius (if authorized above), voltage rating (if authorized above), date of manufacture (or traceable code), flammability rating (if VW-1), oil resistance rating (if 01, 02., 03), inside diameter (before and after recovery for heat-shrinkable tubing), and date of manufacture (or traceable code) printed on tags attached to both ends of the tubing, or printed on the shipping spool label or smallest unit container in which the product is packaged..

Last Updated on 2023-02-24

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2023 UL LLC."