



## OANZ.E492005 - Insulating Tape

## Insulating Tape

See General Information for Insulating Tape

**BM SPA**VIA MILANO 54/56  
20089 ROZZANO, MI ITALY

E492005

Cat. No.	Color	Optional Ratings		
		Flame Retardant+	Sunlight Resistant+	Cold Resistant+
<b>Self-fusing natural rubber insulating tapes. For use with outer covering of friction tape or equivalent</b>				
<b>EAC (#)</b> (@)	Black	No	No	No
<b>Thermoplastic PVC insulating tapes. For use as sole insulation</b>				
<b>ESC (#)</b> (@)	All except clear	Yes	No	Yes
<b>ESD (#)</b> (@)	All except clear	Yes	No	Yes
<b>ETA (#)</b> (@)	Black	Yes	Yes	Yes
<b>ETB (#)</b> (@)	All except black and clear	Yes	Yes	Yes
<b>ETC (#)</b> (@)	Violet, Green, White, Blue, Yellow, Red, Brown, Orange, Gray, Black	Yes	No	No
<b>ETD (#)</b> (@)	Black	Yes	Yes	Yes
<b>ETE (#)</b> (@)	All except clear	Yes	Yes	Yes

+ Complies with "Flame Retardant" and/or "Cold Resistant" and/or "Sunlight Resistant" requirements if authorized in the table above and when so marked.

(#) - May be prefixed by: BM, ETQ, GD, BR

(@) - May be followed by numbers and/or letters that specify width, length and color

Last Updated on 2017-05-04

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"