UL Product iQ™

XCFR2.E70156 - Terminal Blocks - Component

Terminal Blocks - Component

BM SPA E70156
VIA MILANO 54/56
ROZZANO, MI 20089 Italy

Cat. No.	Wire Range	Wire Type	FW	TQ Lb In.	V	A	UG	CA
M093, M093H,	18-12	CU	2	4.4	600	20#1	B,C	2(105),4*
M093/GF, M093H/GF								2(110),4
M093/CS, M093H/CS,	18-12	CU	2	4.4	600	20#1	B,C	2(105),4*
M093GF/CS, M093H/GF-CS								2(110),4
M094, M094GF,	18-10	CU	2	7.0	600	30#2	B,C	2(105),4*
M094/GF, M094GF/CS								2(110),4*
M092, M092/CS,	20-16	CU	2	4.4	600	10#3	B,C	2(105),4
M092GF, M092GF/CS								2(110),4
M095, M095/CS,	18-8 Str 18-10 Sol	CU	2	10.3	600	50	B,C	2(105),4
M095GF, M095GF/CS								2(110),4
N9201, N9201CS	18-14	CU	2	4.4	600	15#4	B,C	2(115)

#1 Rated 30A for Factory Wiring Only.
#2 Rated 40A for Factory Wiring Only.
#3 Rated 15A for Factory Wiring Only.
#4 Rated 25A for Factory Wiring Only.

Marking: Company name or trademark , , , , and catalog designation. (Catalog designation may appear on shipping carton).

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

UL Product iQ™

XCFR8.E70156 - Terminal Blocks Certified for Canada - Component

Terminal Blocks Certified for Canada - Component

BM SPA E70156
VIA MILANO 54/56
ROZZANO, MI 20089 Italy

Cat. No.	Wire Range	Wire Type	TQ Nm	V	A	UG	CA
M095, M095/CS	18-8 Str 18-10 Sol	CU	1.2	600	50	B,C	2(105)
M095GF, M095GF/CS							2(110)
M093, M093H,	18-12	CU	0.50	600	20#1	B,C	2(105)
M093/GF, M093H/GF							2(110)
M093/CS, M093H/CS,	18-12	CU	0.50	600	20#1	B,C	2(105)
M093GF/CS, M093H/GF-CS							2(110)
M094, M094GF	18-10	CU	0.87	600	30#2	B,C	2(105)
M094/GF, M094GF/CS							2(110)
M092, M092/CS,	20-16	CU	0.50	600	10#3	B,C	2(105)
M092GF, M092GF/CS							2(110)
N9201, N9201CS	18-14	CU	0.50	600	15#4	B,C	2(115)

#1 Rated 30A for Factory Wiring Only.
#2 Rated 40A for Factory Wiring Only.
#3 Rated 15A for Factory Wiring Only.
#4 Rated 25A for Factory Wiring Only.

Marking: Company name or trademark , , , , and Recognized Component Mark for Canada, , on the product. Catalog designation, maximum voltage, wire range, and ampere rating appear on the device or, in or on the carton.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"