



## Technical sheet

No. **11FA07A**

Issue  
**V01.0**

**Product family:** Cable-ties - Nylon cable-ties  
**Item code:** BP1536, BP2048  
**Description:** NYLON CABLE-TIES · PUSH MOUNT

### Image



### Specifications

**MATERIAL:** polyamide (PA 6.6)  
**COLOR:** natural  
**INSULATION SELF-EXTINGUISHING:** UL 94 V2  
**OPERATING TEMPERATURE:** from -40 °C to +85 °C  
**MINIMUM INSTALLATION TEMPERATURE:** -10 °C  
**CHEMICAL RESISTANCE:** good resistance to bases, oils, grease, chloride solvents. Limited resistance to acids. Not resistant to phenols.  
**ACCORDING TO STD.:** EN 62275:2015-02  
**CLASSIFICATION:** type 1 (EN), type 21 (UL)  
**ASSEMBLY:** open the package just before use

Code	Width (mm)	Length (mm)	Fixing hole Ø (mm)	Max bundle Ø (mm)	Min bundle Ø (mm)	Tensile minimum resistance (N)	
BP1536	3,6	155	6	37,9	3,5	180	100/2500
BP2048*	4,8	200	8	50,8	3,5	230	100/1500



\* file n° E 223175

**HALOGEN  
FREE**