		Technical sheet		^{№.} 11FA11D		
				Issue	V01.1	
Product family:	Cable-ties -	Nylon accessor	ies			
Item code:	N0901, N09	902, N0903				
Description:	ACCESSOR	IES FOR NYLON	I CABLE-TIES · 2-WAY CA	BLE TIE MOUNTS · U'	V RESISTANT	
	-					
MATERIAL: Color: Insulation Self-e Operating Temper Minimum Installa	RATURE: TION TEMPERATURE:	black UL 94 V2 from -40 °C -10 °C	PA 6.6) + adhesive to +85 °C ince to bases, oils, grease	, chloride solvents. Lii	mited resistance to	o acids. Not resistant to
MATERIAL: COLOR: INSULATION SELF-E OPERATING TEMPEF MINIMUM INSTALLA CHEMICAL RESISTAI	RATURE: TION TEMPERATURE:	black UL 94 V2 from -40 °C -10 °C good resista	to +85 °C		mited resistance to Type of mount	o acids. Not resistant to
MATERIAL: COLOR: INSULATION SELF-E OPERATING TEMPEF MINIMUM INSTALLA CHEMICAL RESISTAI	RATURE: Ition temperature: NCE:	black UL 94 V2 from -40 °C -10 °C good resista phenols.	to +85 °C Ince to bases, oils, grease			
CHEMICAL RESISTA	ATURE: ITION TEMPERATURE: NCE: able ties with max width (mm)	black UL 94 V2 from -40 °C -10 °C good resista phenols.	to +85 °C Ince to bases, oils, grease Height Fixing hole for (mm)) Fixing screw Ø (mm)	Type of mount	Ð