



# Technical sheet

No. **11TD01F**


Issue **V02.0**

**Product family:** Terminals - Uninsulated quick-connect terminals  
**Item code:** 01198, 01199, 02198, 02199, 01298, 01299, 02298, 02299  
**Description:** QUICK-CONNECT TERMINALS · UNINSULATED · PIGGY-BACKS

Image



Technical drawing



## Specifications

**TERMINAL MATERIAL:** tinned/passivated brass  
**ACCORDING TO STD.:** EN 61210: 2010-11  
**OPERATING TEMPERATURE:** da -40 °C a +110 °C

Code	Material	Execution	Section (mm <sup>2</sup> )	Section (AWG/MCM)	For male (mm)	For male (")	W1 (mm)	W2 (mm)	L1 (mm)	L2 (mm)	L3 (mm)	
01198	passivated brass	loose	0.5 ÷ 1	(20 - 18)	6.3 x 0.8	0.250x0.032	6,6	6,3	19,6	7,6	8	100/1000
01199	tinned brass	loose	0.5 ÷ 1	(20 - 18)	6.3 x 0.8	0.250x0.032	6,6	6,3	19,6	7,6	8	
02198	passivated brass	reel	0.5 ÷ 1	(20 - 18)	6.3 x 0.8	0.250x0.032	6,6	6,3	19,6	7,6	8	1300/1300
02199	tinned brass	reel	0.5 ÷ 1	(20 - 18)	6.3 x 0.8	0.250x0.032	6,6	6,3	19,6	7,6	8	
01298	passivated brass	loose	1 ÷ 2.5	(18 - 14)	6.3 x 0.8	0.250x0.032	6,6	6,3	19,6	7,6	8	100/1000
01299	tinned brass	loose	1 ÷ 2.5	(18 - 14)	6.3 x 0.8	0.250x0.032	6,6	6,3	19,6	7,6	8	
02298	passivated brass	reel	1 ÷ 2.5	(18 - 14)	6.3 x 0.8	0.250x0.032	6,6	6,3	19,6	7,6	8	1800/1800
02299	tinned brass	reel	1 ÷ 2.5	(18 - 14)	6.3 x 0.8	0.250x0.032	6,6	6,3	19,6	7,6	8	

