


Product family: Terminals - Insulated quick-connect terminals
Item code: 00198, 00298
Description: QUICK-CONNECT TERMINALS · PVC INSULATED AND ANTI-VIBRATING · PIGGY-BACKS

Image



Technical drawing



Specifications

TERMINAL MATERIAL: tinned brass
END-SLEEVE MATERIAL: copper
INSULATION MATERIAL: polyvinylchloride (PVC)
OPERATING TEMPERATURE: 75 °C max
INSULATION SELF-EXTINGUISHING GRADE: UL 94 V0
RATED VOLTAGE: 300V max
HOW TO ASSEMBLE: double crimping

Code	Color	Section (mm ²)	Section (AWG/MCM)	For male (mm)	For male (")	W1 (mm)	W2 (mm)	L1 (mm)	L2 (mm)	L3 (mm)	L4 (mm)	D1 (mm)	D2 (mm)	
00198		0.25 ÷ 1.5	(22 - 16)	6.3 x 0.8	0.250x0.032	6,6	6,3	22,8	10,5	7,8	8	3,8	1,9	100/1000
00298		1.5 ÷ 2.5	(16 - 14)	6.3 x 0.8	0.250x0.032	6,6	6,3	22,8	10,5	7,8	8	4,3	2,5	50/500

