

**Product family:** Hydraulic equipment - Multi-head  
**Item code:** 200A  
**Description:** CRIMPING HEADSTOCK · FOR MULTI-HEAD PRESS · UP TO 185 mm<sup>2</sup> (SERIES 82)

## Image



## Features

- lateral snap opening for quick and easy die positioning
- the crimping head must be combined with BM 200 manual hydraulic multi-head tool
- it can be combined with a pump using a BM 200CC adapter

## Specifications

**CRIMPING FORCE AT DIE LEVEL:**

50 kN

**DIES:**

82 series

**FIELD OF USE:**

terminals

- uninsulated from 10 to 240 mm<sup>2</sup> (185 mm<sup>2</sup> for DIN)
- uninsulated class 6 and DIN from 10 to 185 mm<sup>2</sup>
- medium voltage from 25 to 150 mm<sup>2</sup>
- aluminum from 16 to 150 mm<sup>2</sup>
- bimetallic from 16 to 150 mm<sup>2</sup>
- bimetallic DIN from 16 to 150 mm<sup>2</sup>
- insulated from 10 to 95 mm<sup>2</sup>
- C shunt from 10 to 35 mm<sup>2</sup>
- end-sleeve from 50 to 150 mm<sup>2</sup>

Code	Description	Length (mm)	Width (mm)	Thickness (mm)	Weight (kg)	Pack size LxWxH (mm)	
200A	50 kN crimping head for BM 200 manual hydraulic multi-head tool including dies-set for uninsulated terminals 10 ÷ 185 mm <sup>2</sup>	130	70	60	1,5	NA	SC

**SERIE82**