

**Product family:** Hydraulic equipment - Pumps and headstocks  
**Item code:** 284, 284L  
**Description:** CRIMPING HEADSTOCK · FOR PUMPS · UP TO 400 mm<sup>2</sup> (SERIES 84)

**Image**




**Features**

- “C” opening for easy joint crimping (the maximum conductor section depends on cable insulation thickness)
- bigger “C” opening in 284L version to crimp big section joints
- with male quick coupling fitting with automatic locking
- for operation it must be combined a pump with an operating pressure of 700 bar

**Specifications**

- CRIMPING FORCE AT DIE LEVEL:** 120 kN  
**DIES:** 84 series  
**FIELD OF USE:** terminals
- uninsulated from 10 to 400 mm<sup>2</sup> (300 mm<sup>2</sup> for DIN)
  - uninsulated class 6 from 10 to 185 mm<sup>2</sup>
  - medium voltage from 25 to 400 mm<sup>2</sup>
  - aluminum from 16 to 240 mm<sup>2</sup>
  - bimetallic from 16 to 300 mm<sup>2</sup>
  - bimetallic DIN from 16 to 300 mm<sup>2</sup>
  - insulated from 10 to 240 mm<sup>2</sup>
  - C shunt from 10 to 150 mm<sup>2</sup>
  - end-sleeve from 50 to 150 mm<sup>2</sup>

Code	Description	Max “C” opening (mm)	Length (mm)	Width (mm)	Thickness (mm)	Weight (kg)	Pack size LxWxH (mm)	
284	120 kN crimping headstock for pump	30	245	115	68	4	440x270x130	VA
284L	120 kN crimping headstock for pump	42	250	130	70	5,3	440x270x130	

**SERIE84**