

**Product family:** Hydraulic equipment - Pumps and headstocks  
**Item code:** 2833  
**Description:** CRIMPING HEADSTOCK · FOR PUMPS · UP TO 240 mm<sup>2</sup> (SERIES 83)

**Image**



**Features**

- lateral snap opening for quick and easy die positioning
- with male quick coupling fitting with automatic locking
- for operation it must be combined with a pump with an operating pressure of 700 bar

**Specifications**

**CRIMPING FORCE AT DIE LEVEL:** 60 kN  
**DIES:** 83 series  
**FIELD OF USE:** terminals

- uninsulated from 10 to 300 mm<sup>2</sup>
- uninsulated class 6 from 10 to 185 mm<sup>2</sup>
- DIN standard from 10 to 240 mm<sup>2</sup>
- NFC standard from 4 to 240 mm<sup>2</sup>
- medium voltage from 25 to 300 mm<sup>2</sup>
- aluminum from 16 to 185 mm<sup>2</sup>
- bimetallic from 16 to 150 mm<sup>2</sup>
- bimetallic DIN from 16 to 185 mm<sup>2</sup>
- insulated from 10 to 95 mm<sup>2</sup>
- C shunt from 10 to 95 mm<sup>2</sup>
- end-sleeve from 50 to 150 mm<sup>2</sup>

Code	Description	Length (mm)	Width (mm)	Thickness (mm)	Weight (kg)	Pack size LxWxH (mm)	
2833	60 kN crimping headstock for pump	230	70	55	1,76	295x155x110	VA

**SERIE83**