	TECHNICAL SHEET	No. 41MA03B Issue V01.2 (EN)

Product family: Terminal blocks - Multiway in nylon

Code: 92CS1, 92CS2, 92CS3, 92CS4, 92CS5, 92CS6, 92CS7, 92CS8, 92CS9, 92CS10, 92CS11, M92CS

Description: MULTIWAY TERMINAL BLOCKS · NYLON · FROM 1 TO 12 WAYS · M092 SERIES WITH WIRE PROTECTION

Image:



Technical Drawing:



Wire protection version of the M092 series

Specifications:

INSULATING HOUSING:	polyamide (PA 6.6) natural color UL 94 V2
CONDUCTIVE BODY:	nickel-plated brass
CAPTIVE SCREW IN:	galvanized steel (M3)
WIRE PROTECTION:	stainless steel
INSULATION SELF-EXTINGUISHING:	EN 60695-2-10 a 850 °C
CONDUCTOR TYPE:	rigid and flexible
TEST VOLTAGE:	2500 V
PROTECTION GRADE:	IP20
ACCORDING TO STD.:	EN 60998-1: 2004, EN 60998-2-1: 2004
WAYS:	12

	Section (mm²)	Section (AWG)	Rated voltage (V)	Test current (A)	Max operating temperature (°C)	Torque (Nm)
03	2,5	-	250/380	24	125	0,25
c UL us	-	20-16	600	10 (*)	105	0,5

* 15 A rated for Factory Wiring Only

Code	Color	L1 (mm)	L2 (mm)	L3 (mm)	L4 (mm)	W1 (mm)	W2 (mm)	S1 (mm)	S2 (mm)	D1 (mm)	D2 (mm)	
92CS1	Natural	5,6 ± 1	8	5,5	2,5	15,2	6	15,3	8,7	3	2,6	
92CS2	Natural	13,5 ± 1	8	5,5	2,5	15,2	6	15,3	8,7	3	2,6	
92CS3	Natural	21,5 ± 1	8	5,5	2,5	15,2	6	15,3	8,7	3	2,6	
92CS4	Natural	30 ± 1	8	5,5	2,5	15,2	6	15,3	8,7	3	2,6	
92CS5	Natural	37,5 ± 1	8	5,5	2,5	15,2	6	15,3	8,7	3	2,6	
92CS6	Natural	45,5 ± 1	8	5,5	2,5	15,2	6	15,3	8,7	3	2,6	Contact BM
92CS7	Natural	54 ± 1	8	5,5	2,5	15,2	6	15,3	8,7	3	2,6	
92CS8	Natural	61,5 ± 1	8	5,5	2,5	15,2	6	15,3	8,7	3	2,6	
92CS9	Natural	69,5 ± 1	8	5,5	2,5	15,2	6	15,3	8,7	3	2,6	
92CS10	Natural	77,5 ± 1	8	5,5	2,5	15,2	6	15,3	8,7	3	2,6	
92CS11	Natural	85,5 ± 1	8	5,5	2,5	15,2	6	15,3	8,7	3	2,6	
M92CS	Natural	93,5 ± 1	8	5,5	2,5	15,2	6	15,3	8,7	3	2,6	50/700

CE

03 c UL us

HALOGEN FREE