


Product family: Terminal blocks - For free connections
Item code: 9924Q, 993Q, 994Q
Description: ONE-WAY TERMINAL BLOCKS · END CONNECTORS · WITH MANUAL TIGHTENING

Image



Technical drawing



Specifications

INSULATING HOUSING: transparent polycarbonate (PC) UL 94 V0
CONDUCTIVE BODY: brass
CAPTIVE SCREW IN: galvanized steel
INSULATION SELF-EXTINGUISHING: EN 60335-1: 2002+A2:2006 (par. 30.2.3), EN 60695-2-10 a 850 °C, EN 60695-2-11
CONDUCTOR TYPE: rigid and flexible
MAX OPERATING TEMPERATURE: 85 °C
PROTECTION GRADE: IP20
ACCORDING TO STD.: EN 60998-1: 2004, EN 60998-2-1: 2004

Code	Conductor section (mm ²)	Connection capability Section (mm ²)	Connection capability N. rigid conductors	Connection capability N. flexible conductors	Rated voltage (V)	Test current (A)	Screw	D1 (mm)	L1 (mm)	W1 (mm)	
9924Q	4	4	2	2	450	32	M4	4,5	10,3	21	20/20
		2,5	2 ÷ 3	2 ÷ 3							
		1,5	2 ÷ 4	2 ÷ 4							
993Q	6	6	2	2	450	41	M4	6	11,8	22,5	20/20
		4	2 ÷ 3	2							
		2,5	2 ÷ 4	2 ÷ 4							
994Q	10	10	2	2	450	57	M6	7,9	14,7	26	20/20
		6	2 ÷ 3	2							
		4	2 ÷ 4	2 ÷ 4							

