

Product family: Conduit fixings - Accessories for spiral conduits
Item code: TP5RGP10, TP5RGN10, TP5RGP12, TP5RGN12, TP5RGP12/13, TP5RGN12/13, TP5RGP14, TP5RGN14, TP5RGP16, TP5RGN16, TP5RGP16/13, TP5RGN16/13, TP5RGP16/16, TP5RGN16/16, TP5RGP20, TP5RGN20, TP5RGP22, TP5RGN22, TP5RGP25, TP5RGN25, TP5RGP28, TP5RGN28, TP5RGP32, TP5RGN32, TP5RGP35, TP5RGN35
Description: IP65 ACCESSORIES FOR SPIRAL CONDUITS · SWIVEL FITTING · PG THREAD · RGP/RGN

Image



Specifications

MATERIAL: fireproof polypropylene
PITCH: PG
RESISTANCE TO SHOCK: class 3 (>2 kg from 10 cm at -5 °C)
MIN. TEMPERATURE: class 2 (-5 °C)
MAX. TEMPERATURE: class 1 (+60°C)
RESISTANCE TO FIRE: self-extinguishing
GLOW WIRE TEST: pass at 850 °C
PROTECTION GRADE: IP65
STANDARD: EN 61386-1, EN 61386-23

Code	Color	PG thread (DIN 40430)	Sheathing diameter (mm)	
TP5RGP10	6971	PG 9	10	10/160
TP5RGN10	6972	PG 9	10	
TP5RGP12	6971	PG 11	12	10/160
TP5RGN12	6972	PG 11	12	
TP5RGP12/13	6971	PG 13.5	12	10/160
TP5RGN12/13	6972	PG 13.5	12	
TP5RGP14	6971	PG 13.5	14	10/100
TP5RGN14	6972	PG 13.5	14	
TP5RGP16	6971	PG 11	16	10/100
TP5RGN16	6972	PG 11	16	
TP5RGP16/13	6971	PG 13.5	16	10/100
TP5RGN16/13	6972	PG 13.5	16	
TP5RGP16/16	6971	PG 16	16	10/100
TP5RGN16/16	6972	PG 16	16	
TP5RGP20	6971	PG 21	20	10/70
TP5RGN20	6972	PG 21	20	
TP5RGP22	6971	PG 21	22	10/60
TP5RGN22	6972	PG 21	22	
TP5RGP25	6971	PG 29	25	10/50
TP5RGN25	6972	PG 29	25	
TP5RGP28	6971	PG 29	28	10/40
TP5RGN28	6972	PG 29	28	
TP5RGP32	6971	PG 36	32	5/20
TP5RGN32	6972	PG 36	32	
TP5RGP35	6971	PG 36	35	5/20
TP5RGN35	6972	PG 36	35	

