

Product family: Conduit fixings - Accessories for spiral conduits
Item code: TP5RGG10, TP5RGGN10, TP5RGG12, TP5RGGN12, TP5RGG14, TP5RGGN14, TP5RGG16, TP5RGGN16, TP5RGG20, TP5RGGN20, TP5RGG22, TP5RGGN22, TP5RGG25, TP5RGGN25, TP5RGG28, TP5RGGN28, TP5RGG32, TP5RGGN32, TP5RGG35, TP5RGGN35, TP5RGG40, TP5RGGN40, TP5RGG50, TP5RGGN50
Description: IP65 ACCESSORIES FOR SPIRAL CONDUITS · SWIVEL FITTING · GAS THREAD · RGG/RGGN

Image



Specifications

MATERIAL: fireproof polypropylene
PITCH: gas
RESISTANCE TO SHOCK: class 3 (>2 kg from 10 cm at -5 °C)
MIN. TEMPERATURE: class 2 (-5 °C)
MAX. TEMPERATURE: class 1 (+60°C)
RESISTANCE TO FIRE: self-extinguishing
GLOW WIRE TEST: pass at 850 °C
PROTECTION GRADE: IP65
STANDARD: EN 61386-1, EN 61386-23

Code	Color	Gas thread (ISO 228/1)	Sheathing diameter (mm)	
TP5RGG10	6971	G 1/4"	10	10/140
TP5RGGN10	6972	G 1/4"	10	
TP5RGG12	6971	G 3/8"	12	10/120
TP5RGGN12	6972	G 3/8"	12	
TP5RGG14	6971	G 1/2"	14	10/100
TP5RGGN14	6972	G 1/2"	14	
TP5RGG16	6971	G 1/2"	16	
TP5RGGN16	6972	G 1/2"	16	
TP5RGG20	6971	G 3/4"	20	10/70
TP5RGGN20	6972	G 3/4"	20	
TP5RGG22	6971	G 3/4"	22	10/60
TP5RGGN22	6972	G 3/4"	22	
TP5RGG25	6971	G 1"	25	10/40
TP5RGGN25	6972	G 1"	25	
TP5RGG28	6971	G 1"	28	
TP5RGGN28	6972	G 1"	28	
TP5RGG32	6971	G 1" 1/4	32	5/25
TP5RGGN32	6972	G 1" 1/4	32	
TP5RGG35	6971	G 1" 1/4	35	5/20
TP5RGGN35	6972	G 1" 1/4	35	
TP5RGG40	6971	G 1" 1/2	40	5/20
TP5RGGN40	6972	G 1" 1/2	40	
TP5RGG50	6971	G 2"	50	5/15
TP5RGGN50	6972	G 2"	50	

