

BATTERY POWERED HYDRAULIC CUTTING TOOL

• 130 kN

38T130




TYPE OF CABLES/ROPES/RODS

copper, aluminum and steel

MAX. PASSAGE

up to \varnothing 45 mm



CUTTING TYPE GUILLOTINE TYPE



LOCKING PIN

enables a secure head closing



Do not use this tool on live cables

Lenght	Width	Height	Weight with battery	Pack size
mm	mm	mm	kg	LxHxH
505	75	330	8,65	594x494x149

FORCE	130 kN
CUTTING TIME	from 10 to 30 seconds
BATTERY	Stanley, Litio, 18V 5.0Ah
MAX. PASSAGE	45 mm



INTERCHANGEABLE BLADES

easy to replace



ROTATIVE HEAD 220°

CUTTING CAPACITY	TYPE OF CABLES	MAX. HARDNESS	MAX. CUTTING Ø
Conductors/Ropes	Copper	< 40 daN/mm ²	\varnothing 45 mm
	Aluminum	< 20 daN/mm ²	\varnothing 45 mm
	Almelec	< 34 daN/mm ²	\varnothing 45 mm
	Steel	< 180 daN/mm ²	7 x \varnothing 3,0 (= \varnothing 9,0)
			19 x \varnothing 2,1 (= \varnothing 10,5)
			19 x \varnothing 2,3 (= \varnothing 11,5)
	Multi-steel strands	< 180 daN/mm ²	\varnothing 18 (strands quantities: 200)
	ACSR (Aluminum conductor steel-reinforced cable)	< 180 daN/mm ²	26 x \varnothing 2,50 + 7 x \varnothing 1,95 (= \varnothing 15,85)
			26 x \varnothing 3,06 + 7 x \varnothing 2,38 (= \varnothing 19,38)
			26 x \varnothing 3,60 + 7 x \varnothing 2,80 (= \varnothing 22,80)
54 x \varnothing 3,50 + 19 x \varnothing 2,10 (= \varnothing 31,50)			
54 x \varnothing 4,36 + 19 x \varnothing 2,62 (= \varnothing 39,20)			
Bars	Steel	< 60 daN/mm ²	\varnothing 20
		< 42 daN/mm ²	\varnothing 22
	Copper	< 30 daN/mm ²	\varnothing 33
		< 25 daN/mm ²	\varnothing 35
Aluminum	< 16 daN/mm ²	\varnothing 45	



Case and charger delivered with the tool.

